

Facsimile Communication Form To Sales Dept., KANETEC Co., Ltd

※For inquiry, please make a copy of this form.

Electromagnetic Holder Selection Data

Date of transmission	Page
	/ pages

Company name		Section		Name	
Address	〒				
Tel	—	—	Fax	—	—

Magnetic holder

Model		Quantity required	
Documents	• Attached (sheets) • None	Sample	• Available () • Not available
Installation site	• Indoor • Outdoor (Drip-proof: Required Not required)	Witnessed inspection	• Required (plant, field,) • Not required
Ambient temperature	• Normal, High temp. °C	Guidance	• Required (meeting, installation, trial run) • Not required
Required shape	• Round • Rectangular • Others ()	Paint color	• KANETEC standard, Specified color ()
Operating hour	• hours / day	Working rate	• Run minutes — pause minutes, continuous

Workpiece to convey

Documents	• Attached (sheets) • None	Dimensions	• W× D× Hmm
Temperature	• Normal, High °C	Mass	• Approx. (g, kg)
Material	• SS or SPC • S45C • FC • Tool steel • Others ()		
Surface roughness	• ~ • ▽ • ▽▽ or better • As cast • Plated • Paint film thickness (μm)		

Description of workpieces to convey	Shape of workpiece (sketch)
Stacked: Yes • No	
Oil adhesion: Yes • No	
Use of Floater: Yes • No	
Automatic M/C: Yes • No	

Control unit

Model		Quantity required	
Power source	• phase VAC Hz	Paint color	• Kanetec standard, Specified color ()
Installation site	• Indoor • Outdoor (Drip-proof: Required Not required)	Ambient temperature	• KANETEC standard, High temp. °C
Reverse excitation	• Required • Not required	Voltage adjustment	• Required (Output switchover, output variable) • Not required
Remote operation box	• Required • Not required	Operating method	• Operation panel • Remote operation (pushbutton, external signal)

Conveyance equipment

Equipment name	• Manual operation, Automatic machine ()	Conveyance interval	• mm, sec.
Conveyance speed	• m/min	Accuracy	

Remarks

--