

Facsimile Communication Form To Sales Dept., KANETEC Co., Ltd

※For inquiry, please make a copy of this form.

Lifting Magnet Selection Data

Date of transmission	Page
	/ pages

Company name		Section		Name	
Address	〒				
Tel	—	—	Fax	—	—

Model		Quantity required		
Documents	• Attached (sheets) • none	Sample	• Available • Not available	
Installation site	• Indoor • Out door	Witnessed inspection	• Required (plant,field,) • Not required	
Ambient temperature	• Normal °C	Guidance	• Required (meeting,installation, trial run) • Not required	
Power source	• phase VAC Hz	Paint color	• KANETEC standard,Specified color ()	
Supplies	• Provided () • Not provided	Operating hour	• hours / day	
Specified by manufacturer	• Specified () • Not specified	Documents to submit		
Use hours	• Run minutes — pause minutes			
Description of work	• Draining • Sorting • Scrapping • Others ()			
	• Lifting lumps lumps • Lifting sheets sheets			
Workpiece	Material	• SS • SPCC • S45C • FC • others ()		
	Temperature	• °C		
	Shape	• ~ • ▽ • ▽▽or better • As cast • Shot • Plated • Paint film thickness μm		
		• Plate • Pipe • Round bar • Thin sheet • Section steel (Attracting part to be specified)		
Dimension		• Length Min. mm – Max. mm • Width (Dia.) Min. mm (φ) – Max. mm (φ) • Thickness Min. mm –Max. mm		
Mass	• Min. kg — Max. kg			
Crane	• tons	Lifting height	m	
Required type	• Electromagnet • Permanent magnet • Permanent electromagnet • Battery			
	Magnet installation	• Chain • Hinge • Tap		
	Beam (Used/ Not used)	If used	• Expandable • Mobile magnet (automatic,manual) • Fixed	
		Manual	• Hinge type • Trolley type	
Lifting method	• Wire • Hinge only • Bolting			

Power panel

Panel Specifications	Model		Quantity required	
	Construction	• Indoor • Outdoor • Dustproof (air) • Drip-proof (air) Panel • Others ()		
	Installation site	• Electrical room • On machine • Outdoor • On crane • Others ()		
	Size	• Specified (W × D × H mm) • Not specified		
	Environmental temperature	• Normal Max. °C – Min. °C		
	Paint color	• KANETEC standard、 Specified color ()		
	Remote operation box	• Required () • Not required		
Operation site	• Ground • Crane operator cab • Others ()			
Circuit specifications	Power source	• phase VAC Hz		
	Output voltage variation	• Required (Submit specified circuit diagram) • Not required		
	Uninterruptible power supply	• Required • Not required	Guaranteed power uninterruptible time	• 5min. • 10min. • 15min. • 20min. • 30min. • min.
	Reverse excitation	• Required • Not required	Reverse excitation method	• Manual • Automatic
	Control circuit voltage	• Specified (V) • Not specified		
	Operating method	Operation on panel	Specified circuit: • Required (Submit specified circuit diagram) • Not required (Determined by KANETEC)	
External signal operation		Specified circuit: • Required (Submit specified circuit diagram) • Not required (Determined by KANETEC)		
Output signal	Required (Submit specified circuit diagram) • Not required			
Accessories	• Required (Select one from below) • Not required			
	• Operation switch • Pushbutton switch • Cam switch • Controller			
	• Cable reel • Cable connector • Others ()			
Remarks				